


# Technical data sheet

## Fine power protection for Modul 45 with acoustic function display

Item number: 6117473



Surge protection/network fine protection, type 3, according to EN 61643-11 for installation in Rapid 45 duct, device installation duct and underfloor systems.

- Version-O with acoustic function display
- Quick and easy mounting
- Low construction width of 22.5 mm
- Colour: Pure white; RAL 9010

Application: The surge protective device secures downstream and nearby sockets.  
Surge protection device type 3 (class D) to VDE 0675, Parts 6–11 (DIN EN 61643-11).  
For installation in Rapid 45 trunking, device installation trunking and underfloor systems.



### Master data

Item number	6117473
Type	ÜSS 45-O-RW
Description 1	Surge protective Modul 45
Description 2	with optical display
Manufacturer	OBO
Dimension	255V
Colour	Pure white; RAL 9010
Smallest sales unit	1
Unit of quantity	Piece
Weight	2.411 kg
Weight unit	kg/100 pc.


# Technical data sheet

## Fine power protection for Modul 45 with acoustic function display

Item number: 6117473



### Technical data



Arrester surge current (8/20 $\mu$ s) [total]	5 kA
Response time	<25 ns
Blow-out	no
Version for	Visualfunction display
Operating temperature, max.	45 °C
Operating temperature, min.	-25 °C
Remote signalling	no
Combined voltage protection level [L-PE]	1500 kV
Maximum continuous voltage AC	255
Conductor cross-section, rigid (single-wire/multiwire), max.	1.5 mm <sup>2</sup>
Conductor cross-section, rigid (single-wire/multiwire), min.	1.5 mm <sup>2</sup>
Lightning protection zone LPZ	2→3
Max. mains-side overcurrent protection	16
Maximum back-up fuse	16 A
Maximum discharge current (8/20 $\mu$ s)	5 kA
Installation type	Module
Nominal discharge current (8/20 $\mu$ s)	2.5 kA
Nominal voltage AC (50/60 Hz)	230 V
Network form	Other
OBO_Nominal load current (input/output terminal)	16 A
Test class, type 3	yes
Protection rating	IP20
Protection level	≤1,5
Protection level [L-N]	≤1500
Protection level [N-PE]	1.5 kV
Signalling on device	Visual
SPD to EN 61643-11	Type 3
SPD to IEC 61643-1	Class III