

Technical data sheet

Bolt tie BZ-U A4

Item number: 3498336



Bolt tie BZ for the anchoring of medium-duty to heavy-duty loads, indoors and outdoors, both in cracked and non-cracked concrete. It combines high approved loads with small edge distances and axial spacings.
European Technical Approval ETA-99/0010, including characteristic values under fire exposure to fire resistance R 120.
Proof of suitability in the case of seismic impacts, categories C1 and C2.
Shock approval by the Federal Office for Civil Protection in Bern, Switzerland.




A4	Stainless steel
2B	Bright, treated

Master data

Item number	3498336
Type	BZU10-10-30/90A4
Description 1	Wedge anchor BZ-U
Manufacturer	OBO
Dimension	M10x90mm
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	50
Unit of quantity	Piece
Weight	6.74 kg
Weight unit	kg/100 pc.

Dimensions



Length	90 mm
Dimension L	90 mm

Technical data sheet

Bolt tie BZ-U A4

Item number: 3498336



Technical data

Version for	For knocking in
Anchor/nail/bolt version	Spreading anchor
Drill hole depth	75 mm
Drill hole diameter, min.	10 mm
Thread	M10
Thread metric	10
Thread type	Metric
Clamping strength	10 mm
Permitted load range, tension zone	4.3
Clamping range, max.	30 mm
Clamping range, min.	10 mm

Standard anchoring depth

	M8-10/75			
	46			
mm	8	8	10	-
mm	40	40	75	-
mm	10	30	10	-
KN	2.4	2.4	4.3	-