

# Technical data sheet

## GRAF9 universal service outlet, wet-cleaned with structured lid

Item number: 7405750



Service outlet with tube body for wet-cleaned floors for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in duct and trunking systems and system floors indoors.

Up to 9 installation devices can be used with a 50 mm central plate.

Service outlet with tube body for wet cleaned floors, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed.



**AIG** Cast aluminium

### Master data

|                     |                             |
|---------------------|-----------------------------|
| Item number         | 7405750                     |
| Type                | GRAF9-2 U 9011              |
| Description 1       | Service outlet for wet care |
| Description 2       | with structured lid         |
| Manufacturer        | OBO                         |
| Dimension           | Ø325x74                     |
| Colour              | Graphite black; RAL 9011    |
| Material            | Cast aluminium              |
| Smallest sales unit | 1                           |
| Unit of quantity    | Piece                       |
| Weight              | 246 kg                      |
| Weight unit         | kg/100 pc.                  |

### Technical data

|                                 |                     |
|---------------------------------|---------------------|
| Number of installable devices   | 12                  |
| Number of mounting boxes        | 3                   |
| Version for                     | Round               |
| Cable outlet version            | Lowerable tube body |
| Floor covering protection frame | yes                 |
| Floor care                      | Wet                 |
| Seal installation option        | yes                 |

# Technical data sheet

GRAF9 universal service outlet, wet-cleaned with structured lid

Item number: 7405750



## Technical data

|   |                         |
|---|-------------------------|
| Floor height, min.                                | 80 mm                   |
| Suitable for raised floor installation            | yes                     |
| Suitable for screed-flush closed underfloor ducts | yes                     |
| Suitable for screed-covered underfloor ducts      | yes                     |
| Suitable for cavity floor installation            | yes                     |
| Suitable for wet care                             | yes                     |
| Suitable for underfloor box                       | 350                     |
| Suitable for underfloor ducts                     | yes                     |
| With floor covering recess                        | no                      |
| Nominal size for device installation units        | R9                      |
| Frame version                                     | Carpet protection frame |
| Protection rating (IP) when used                  | IP20                    |
| Protection rating (IP) when unused                | IP45                    |
| Protection rating IK code                         | IK10                    |
| Heavy-duty version                                | yes                     |
| Installation system type                          | UT4                     |
| Vertical load, large area                         | to 10,000 N             |
| Vertical load, small area                         | to 3,000 N              |
| Approvals   | VDE                     |
| Opening mechanism                                 | Sash lock               |