## **Technical data sheet**

### T branch piece, duct height 40 mm, FS

**Item number: 7218074** 



Tee with intumescent fire protection mesh for PYROLINE® Rapid PLM installation duct. Suitable for direct wall and ceiling mounting, mounting below system floors and on support systems. Tool-free joint mounting with PLM SI joint connector. The cover is snapped on without tools, allowing rapid inspection and retroassignment. The cover overhang allows offset cover mounting for continuous equipotential bonding of the entire duct section.



 $\epsilon$ 

St

Steel

FS

Strip galvanized

### Master data

Item number	7218074
Туре	PLM TB 0410 FS
Description 1	T-branch
Description 2	with fire protection mesh
Manufacturer	OBO
Dimension	500x300x40
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	135.8 kg
Weight unit	kg/100 pc.

#### **Dimensions**

Dimension A	300 mm
Dimension B	100 mm
Dimension H	40 mm
Dimension t	500 mm

# **Technical data sheet**

# T branch piece, duct height 40 mm, FS

**Item number: 7218074** 



Technical data		
	Number of flammable sides	4
	Classification EI – installation duct	90
	With perforation	yes
	Usable cross-section	1780 mm²
	Partitions possible	yes
	Jacketing	Steel