

Technical data sheet

Aluminium pipe, without thread

Item number: 2046004



Electrical installation pipe without threaded ends to EN 61386-1 for mechanical protection of cables. With burr-free inner wall.



Alu Aluminium

Master data

| | |
|---------------------|-------------------|
| Item number | 2046004 |
| Type | S25W ALU |
| Description 1 | Aluminium conduit |
| Description 2 | without thread |
| Manufacturer | OBO |
| Dimension | Ø25, 3000mm |
| Material | Aluminium |
| Smallest sales unit | 30 |
| Unit of quantity | Metre |
| Weight | 26.134 kg |
| Weight unit | kg/100 m |


Technical data sheet

Aluminium pipe, without thread


Item number: 2046004



Dimensions



| | |
|------------------|----------|
| Length | 3,000 mm |
| Dimension D | 25 mm |
| Dimension L | 3,000 mm |
| Dimension m (mm) | M25 |
| Dimension t | 1.3 mm |



Technical data

| | |
|-----------------|----------------------|
| Surface-mounted | yes |
| Pipe version | Rigid without thread |

Technical data sheet

Aluminium pipe, without thread

Item number: 2046004



Technical data

| | |
|--|-----------------------|
| Concrete installation | yes |
| Bending behaviour | rigid |
| Pressure resistance | Heavy (1,250 N) |
| Use temperature, max. | + 250 °C |
| Use temperature, min. | - 45 °C |
| Cavity wall installation | yes |
| Installation on wood | yes |
| Installation in the earth | yes |
| Installation outdoors | yes |
| Classification code | 44561 |
| Machines and system installation | yes |
| With sleeve | no |
| Brushed surface | no |
| Polished surface | no |
| Impact resistance | Heavy (2.0 kg/300 mm) |
| Permitted temperature range, max. | 250 °C |
| Permitted temperature range, min. | -45 °C |
| Underfloor installation (bitumen, hot asphalt) | yes |
| Underfloor installation (screed) | yes |
| Concealed | yes |