Technical data sheet Junction box T 40, closed

Item number: 2007223





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Square design without entries. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. With fixed clamping cover. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK07 according to DIN EN 50102.



Master data

Item number	2007223
Туре	T 40 OE
Description 1	Junction box
Description 2	without insertion opening
Manufacturer	OBO
Dimension	90x90x52
Colour	Light grey; RAL 7035
Material	Polypropylene
Smallest sales unit	5
Unit of quantity	Piece
Weight	6.3 kg
Weight unit	kg/100 pc.

Technical data sheet Junction box T 40, closed

Item number: 2007223





Technical data

ExpandableyesType of insertionNoneType of entryCableType of housing penetrationWithoutMeasured insulation voltage Vi500 VEquipmentWithoutCoverNot transparentCover fasteningLockingEntry from rearyesEntriesNoneExplosion-tested versionno
Type of entryCableType of housing penetrationWithoutMeasured insulation voltage Vi500 VEquipmentWithoutCoverNot transparentCover fasteningLockingEntry from rearyesEntriesNone
Type of housing penetration Without Measured insulation voltage Vi 500 V Equipment Without Cover Not transparent Cover fastening Locking Entry from rear yes Entries None
Measured insulation voltage Vi 500 V Equipment Without Cover Not transparent Cover fastening Locking Entry from rear yes Entries None
Equipment Without Cover Not transparent Cover fastening Locking Entry from rear yes Entries None
Cover Not transparent Cover fastening Locking Entry from rear yes Entries None
Cover fastening Locking Entry from rear yes Entries None
Entry from rear yes Entries None
Entries None
Explosion-tested version no
Flame-resistant Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C
Shape Square
Maintain electrical functions Without
For Ex zone Without
For Ex zone gas Without
For Ex zone dust Without
Fibre-glass reinforced no
Halogen-free yes
Clear internal dimensions 77x77x46 mm
With screening no
with lid yes
Mounting type Wall/ceiling mounting
Nominal cross-section, min. 4 mm ²
Nominal voltage 500 V
Sealable no
Protection rating IP56

Junction box T 40, closed

Item number: 2007223



Technical data

Protection rating IK code	IK07.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Weatherproof	no